



# Recessed Lighting

## 6" Shallow/Low-Plenum Downlighting

For New Work Applications



For Remodel Applications



Insulated Can - For New Work Applications



### STANDARD 11-R6PLNAT FEATURES

- 6-1/2"W x 5-1/2"H
- Thermally-protected
- Adjustable housing for various ceiling thickness
- "Nailless" installation bar hangers (new work)
- Integral T-Bar installation slots (new work)
- Adjustable lamp height
- UL listed for feed-through wiring and damp location
- Oversized pre-wired snap on J-Box with 4 integral Romex pry-outs with strain reliefs

### 11-R6PLNAT

For new work applications where low-plenum or 6" joists are present 3-inch clearance of insulation required.

### 11-R6PLRAT

For old work or remodel applications where low-plenum or 6" joists are present 3-inch clearance of insulation required.

### 11-R6LPNATIC

For new work applications and where low-plenum or 6" joists are present for direct contact with insulation.

## OPTIONS

- When ordering, specify suffix:
- "AT" for air-tight housing
  - "Q" for quick connector
  - "N" for nail hanger bars

## TRIMS



Fresnel Lens  
8" O.D.  
60W/A19



Eyeball - white  
8" O.D.  
75W/R30 or PAR 30  
(Specify SN for satin nickel)



Eyeball - polished brass  
8" O.D.  
75W/R30 or PAR 30  
(Specify SN for satin nickel)



Black stepped baffle  
8" O.D. wide ring  
75W/R30 or PAR 30



Black stepped baffle  
7" O.D.  
75W/R30 or PAR 30  
(Specify SN for satin nickel)



Wallwash black baffle  
8" O.D.  
75W/R30 or PAR 30



White stepped baffle  
7" O.D.  
75W/R30 or PAR 30



Satin Nickel stepped baffle  
7" O.D.  
75W/R30 or PAR 30



Albalite shower  
8" O.D.  
40W/A19  
(Specify SN for satin nickel)



Dropped opal shower  
8" O.D.  
40W/A19



Open trim - white  
8" O.D.  
75W/R30 or PAR 30  
(Specify PB for polished brass)



Open trim - satin nickel  
8" O.D.  
75W/R30 or PAR 30